



AAT



Removable Reflective Cap

Design Features

- Spray Angle : 120° /150° /180°
- Spray Pattern : Hollow cone- shaped spray pattern with a ring-shaped impact area.
- Drops : Small- to medium-size,uniform distribution over a wide range of flow rates and pressure.
- Material : BRASS/SS
- Features : Interchangeable spray caps within each inlet connection size group for maximum versatility.

Order Info

AAT	—	3/4	—	SS	—	4	—	120
Nozzle Type		Inlet Conn		Material Code		Capacity Size		Spray Angle

For NPT threaded connections, add the letter "N "before the nozzle connection size.

Applications

- Water aerating
- Degreasing
- Dust control
- Metal treating
- Gas cooling & scrubbing
- Washing & cooling

Performance State

At the stated pressure in bar.

Inlet Conn (in.)	Capacity Size	Flow Rate Capacity(L/min)						
		0.4bar	0.7bar	1.5bar	3bar	4bar	6bar	7bar
1/8	0.37	1.1	1.4	2.1	3.0	3.4	4.2	4.5
	0.5	1.4	1.9	2.8	4.0	4.6	5.6	6.0
	0.75	2.2	2.9	4.2	5.9	6.8	8.4	9.0
1/4	1	2.9	3.8	5.6	7.9	9.1	11.2	12.1
	1.5	4.3	5.7	8.3	11.8	13.7	16.8	18.1
	2	5.8	7.7	11.2	15.8	18.2	22	24
	2.5	7.2	9.5	13.9	19.7	23	28	30
3/8	3	8.8	11.6	17.0	24	27	34	36
	3.5	10.4	13.7	20	28	32	39	42
	4	11.9	15.7	23	32	36	45	48
	4.5	12.9	17.1	25	36	41	50	54
	5	14.4	19.1	28	39	46	56	60

· Special size please consult our sale dept!