



Dry Mist Humidifier WMD



Features

- Spraying distance of 4M or more;
- Can prevent drying and static electricity generation;
- More energy efficient than other humidification methods.

Applications

- Workshop anti-static cooling and humidification.
- Farm disinfection
- Garden irrigation
- Cooling and dust removal

Performance State

· Siphon Type

Model Number	Air cap Orifice	Liquid Orifice	Air Press.	Air consumption	Liquid Capacity	GraininessSMD (1meter)
GWJSQ-WJB-316L-0.4K	0.4	0.4	2KG	6m ³ /H	0.1L/min	10μm
	0.4	0.4	3KG	8m ³ /H	0.11L/min	8μm
	0.4	0.4	4KG	10m ³ /H	0.12L/min	7μm
GWJSQ-WJB-316L-0.7K	0.5	0.7	2KG	6m ³ /H	0.19L/min	8μm
	0.5	0.7	3KG	7m ³ /H	0.2L/min	8μm
	0.5	0.7	4KG	8m ³ /H	0.21L/min	9μm
GWJSQ-WJB-316L-0.8K	0.5	0.8	2KG	6m ³ /H	0.21L/min	7μm
	0.5	0.8	3KG	6.8m ³ /H	0.22L/min	8μm
	0.5	0.8	4KG	7.5m ³ /H	0.23L/min	9μm

· Pressure Type

Model Number	Air cap Orifice	Liquid Orifice	Air Press.	Water press.	Air consumption	Liquid Capacity	GraininessSMD (1meter)
GWJSQ-WMD-316L-0.4K	0.4	0.4	3KG	1.2KG	7.5m ³ /H	0.2L/min	8μm
				1.5KG	7.5m ³ /H	0.4L/min	12μm
	0.4	0.4	4KG	1.2KG	9m ³ /H	0.2L/min	9μm
				1.5KG	9m ³ /H	0.4L/min	14μm
GWJSQ-WMD-316L-0.7K	0.5	0.7	3KG	1.2KG	9m ³ /H	0.1L/min	8μm
				1.5KG	9m ³ /H	0.38L/min	9μm
	0.5	0.7	4KG	1.2KG	10.8m ³ /H	0.18L/min	7μm
				1.5KG	10.8m ³ /H	0.38L/min	7μm
GWJSQ-WMD-316L-0.8K	0.5	0.8	3KG	1.2KG	10m ³ /H	0.18L/min	10μm
				1.5KG	10m ³ /H	0.39L/min	10μm
	0.5	0.8	4KG	1.2KG	11.5m ³ /H	0.18L/min	8μm
				1.5KG	11.5m ³ /H	0.39L/min	9μm

Dry Mist Humidifier WJB



Advantage

- Pa66 Industrial nylon material. Acid-proof, alkali-proof, explosion-proof; .
- Good sealing, no water leakage;
- The metal part is 316 stainless steel material;
- Particle size test report can be issued;
- All assembled finished products, 100% inspection and shipment.